



## **Velvex Trans-Gear EP 140**

### **DESCRIPTION**

Velvex Trans-Gear EP 140 is hypoid Gear oils formulated to give good oxidation stability for long service life. These oils contain Extreme pressure (EP) additives to withstand high temperature and High load, encountered during power transmission. In addition, it also contains Pour point depressant to prevent the lubricant from channeling at low temperature. These are manufactured from selected high quality base oils.

### **APPLICATION**

Velvex Trans Gear EP 140 oil is ideal for manual transmissions; rear axle, automotive hypoid gear units and fluid lubricated universal joints. Recommended for Maruti, HM, Ashok Leyland, Tata Motors, Eicher, M & M, TAFE, Swaraj, Escorts, etc.

### **BENEFITS**

- Maximizes equipment life by resisting gear wear and scuffing
- Long service life by resisting oxidation and oil thickening
- Protection against corrosion of ferrous and non-ferrous components
- Prevent loss of lubricant due to foaming

### **PERFORMANCE LEVEL**

API GL-4, MIL-L-2105, IS 1118:92 EP Type GL-4

### **TYPICAL PROPERTIES**

Sr No.	Parameters	Velvex Trans-Gear EP 140
1	Appearance	Clear and Bright
2	Kinematic Viscosity@100°C,cSt	28 – 34
3	Viscosity Index ,Min.	90
4	Flash Point, COC,°C,Min.	190
5	Copper Corrosion @100°C For 1 Hr	Max 2b

These are typical figures and do not constitute a specification .In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Nandan Petrochem Ltd. Rev 01-01/04/2015