



Velvex Trans-Gear EP 85W140

DESCRIPTION

Velvex Trans-Gear Super EP 85W-140 oil is extreme pressure automotive gear oil. This oil is blended from selected base stocks and contains Extreme Pressure (EP) additives to withstand high temperature and pressure encountered during power transmission.

APPLICATION

Velvex Trans Gear Super EP 85W-140 oil is ideal for manual transmissions; rear axle, automotive hypoid gear units and fluid lubricated universal joints. Recommended for Maruti, HM, Ashok Leyland, Tata Motors, Eicher, M&M, TAFE, Swaraj, Escorts, etc.

BENEFITS

- Maximizes equipment life by resisting gear wear and scuffing due to good EP characteristics
- Long service life by resisting oxidation and oil thickening
- Protection against corrosion of ferrous and non-ferrous components
- Prevents loss of lubricant from foaming

PERFORMANCE LEVEL

API GL-5, MIL-L-2105 D, IS 1118:92 EP Type GL-5

TYPICAL PROPERTIES

Sr No.	Parameters	Velvex Trans-Gear EP 85W140
1	Appearance	Clear and Bright
2	Kinematic Viscosity@100°C,cSt	28.0-34.0
3	Viscosity Index ,Min.	90
4	Flash Point, COC,°C,Min.	180
5	Copper Corrosion @121°C For 3 Hrs	3 max
6	Pour point,°C,Max.	(-)15

These are typical figures and do not constitute a specification .In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Nandan Petrochem Ltd. Rev 01-01/04/2015