



VELVEX CNG SUPREME 20W50

DESCRIPTION

Velvex CNG 20W-50 is formulated to meet API SF / CD performance requirement. It is blended using high quality base oils, shear stable viscosity improver, performance proven engine oil additives and pour point depressant. It is multigrade engine oil for use all round the year.

APPLICATION

Velvex CNG 20W-50 is recommend for use in all LPG /CNG/ Petrol engines of passenger cars, 3-wheeler and small delivery vans.

BENEFITS

- Compatible with alternative fuel.
- Excellent TBN retention.
- Low ash forming.
- Provides exceptional control of deposit, oil oxidation.

PERFORMANCE LEVEL

This Product meets API SF/CD requirements.

TYPICAL PROPERTIES

Sr No.	Parameters	Velvex CNG Supreme 20w-50
1	Appearance	Clear and Bright
2	Kinematic Viscosity@100°C,cSt	17.00 -18.0
3	Viscosity Index ,Min.	120
4	Flash Point, COC,°C,Min.	200
5	TBN mg KOH/gm.,Min.	4.2
6	Pour Point, °C, Max.	(-)21

These are typical figures and do not constitute a specification .In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Nandan Petrochem Ltd. Rev 01-01/04/2015