



Velvex Zoom Premium 4T 20W-40 API SM

DESCRIPTION AND APPLICATION

Velvex Zoom Premium 4T 20W-40 is universal oil for Engine, Clutch and Gear of Motorcycle . It is formulated for high speed air-cooled engines of new generation Motorcycles and scooters .Zoom Premium 4T 20W-40 exceeds the most stringent performances requirements of JASO MA2 and the valve train wear requirements of API SM

BENEFITS

The Life boosting additives in Zoom Premium 4T 20W-40 Ensures

- Maxi mum Power
- Smooth drivability
- Lowers Engine maintenance Cost
- Excellent wear and oxidation protection
- Withstands higher sump temperature of 130°c

PERFORMANCE LEVEL

API SM, JASO MA2

TYPICAL PROPERTIES

Sr No.	Parameters	Velvex Premium 4T 20W-40
1	Appearance	Clear and Bright
2	Kinematic Viscosity@100°C,cSt	14.00 -15.5
3	Viscosity Index ,Min.	110
4	Flash Point, COC,°C,Min.	220
5	TBN mg KOH/gm.,Min.	6.0
6	Pour Point, °C, Max.	(-)21

These are typical figures and do not constitute a specification .In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Nandan Petrochem Ltd. Rev 01-01/04/2015