



Velvex UTTO

DESCRIPTION

Velvex UTTO (Universal Transmission Fluids) is high performance fluid for use in transmissions, hydraulic systems, oil immersed brakes of tractors and off-highway equipment. Velvex UTTO is specially designed for use where a common lubricant reservoir serves transmissions, final drivers and hydraulic systems and to optimize the performance of agricultural and commercial tractors. These fluids meet the specifications of major equipment manufacturer's tractors.

APPLICATION

Recommended for use in Heavy Duty Tractor transmission with wet break, used in off-highway equipment's in agriculture, construction quarrying. Can be used in transmission application requiring API GL-4 oil except in hypoid gear designs.

BENEFITS

- Superior friction durability & ensures Noise free operation, smooth & effective Braking.
- Excellent anti wears Properties and extreme pressure properties, controls wear
- Extends equipment life and reduce maintenance costs
- Excellent protection against rust and corrosion.
- Advanced final drive performance.

PERFORMANCE LEVEL

API GL-4, J20 C, Ford New Holland: M2C 134D, Massey Ferguson: M1141, Caterpillar: TO-2, DDA C-4

TYPICAL PROPERTIES

Sr No.	Parameters	Velvex UTTO
1	Appearance	Clear & Bright
2	Kinematic Viscosity@100°C,cSt	10.0-11.5
3	Viscosity Index ,Min.	108
4	Flash Point, COC,°C,Min.	220
5	Pour point,°C,Max.	(-27)
6	Copper Corrosion, @150°C 3 hrs , Max.	2