



Velvex Super Power 20W-40 HDMO

DESCRIPTION

VELVEX SUPER POWER 20W 40 is top tier multi-grade diesel engine crankcase oil manufactured from premium quality virgin base stock. It is fortified with a shear stable viscosity index improver and high performance engine oil additives. It also contains a special additive to retard soot induced oil thickening, particularly for engines emitting black exhaust smoke. As a result, oil in service does not thicken much, while the engine runs over a longer period.

APPLICATION

VELVEX SUPER POWER 20W 40 is recommended as extended drain service engine oil for new generation diesel engines meeting Bharat I/Euro I emission norms, manufactured by caterpillar, Cummins, Tata Motors, Ashok Leyland, Swaraj Mazda, Eicher, Ford, Toyota, Simpson etc.

BENEFITS

- Extends engine life
- Resists oil thickening
- Reduces fuel consumption
- Reduces maintenance cost
- Protects from rust and corrosion
- Prevents carbon built-up in engines

PERFORMANCE LEVEL

API CF-4/SG, ACEA E2-96, MB 228.1, MAN 271, MACK EO-K2, IS 13656:2002 Type EDL 5

TYPICAL PROPERTIES

Sr No.	Parameters	Velvex SUPER POWER 20W-40
1	Appearance	Clear and Bright
2	K.V. 100°C,cSt	14.0-15.0
3	Viscosity Index Min.	110
4	Flash Point, COC, °C	220
5	TBN mg KOH/gm.	8.0 Min.
6	Pour Point,°C	(-)21Max

These are typical figures and do not constitute a specification .In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Nandan Petrochem Ltd. Rev 01-01/04/2015