



Velvex Red Gel Grease No.3 (NLGI 3)

DESCRIPTION

VELVEX Red Gel GREASE No.3 specially developed for the automotive segment to meet the requirements of a long life gel grease. It is formulated with synthetic base oils, specially thicker technology and high performance additives to fulfil the mechanical and thermal requirements of automotive wheel hubs and extreme performance conditions

APPLICATION

VELVEX Red Gel GREASE No.3 is recommended for use in wheel bearings of all passenger cars, Trucks, Busses, Farm equipment, on highway and off Highway commercial vehicles and Machinery.

Benefits

- Outstanding Mechanical and Thermal Stability under extreme conditions
- Superior Corrosion and Extreme pressure protection to enhance the component life
- Excellent Product stability both at storage and service conditions

PERFORMANCE LEVEL

Meets IS - 12203-1999 (RA 2004) requirements

Typical Properties

1	Appearance	Visual	Homogenous
2	Texture	Visual	Smooth
3	Colour	Visual	RED
4	Soap Type	Flame test	Lithium
5	Penetration at 25°C, worked (60X)	D - 217	240 - 270
6	Dropping Point	D 566	190

These are typical figures and do not constitute a specification. In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of NANDAN Petrochem Ltd. Mumbai , 02, 12/08/2021