



## **Velvex Multi Grade 20W-40**

### **DESCRIPTION**

Velvex Multi Grade 20W-40 is an all season, multigrade crankcase diesel engine oil designed for severe service conditions. It is formulated from high VI, highly refined base oils combined with ash less dispersant, metallo- organic detergent and effective corrosion and oxidation inhibitor.

### **APPLICATION**

It is recommended for use in LCVs, Trucks and Buses of Tata Motors, Ashok Leyland, Eicher, Mahindra, Swaraj Mazda, etc. powered with pre 'India 2000' engines. Suitable for use in both naturally aspirated and turbocharged diesel engines operating under severe service conditions.

### **BENEFITS**

- Minimizes Deposits
- Prevents Rust & Corrosion
- Reduces engine components wear
- Reduces maintenance cost

### **PERFORMANCE LEVEL**

API CF

### **TYPICAL PROPERTIES**

Sr No.	Parameters	Velvex Multigrade 20W-40
1	Appearance	Clear and Bright
2	Kinematic Viscosity @100°C,cSt	14-15.5
3	Viscosity Index ,Min.	110
4	Flash Point, COC,°C,Min.	200
5	TBN mg KOH/gm,Min.	4.0
6	Pour Point, °C, Max.	(-)21

These are typical figures and do not constitute a specification .In pursuit of continuous improvement, these figures may be changed without notice at the sole discretion of Nandan Petrochem Ltd. Rev 01-01/04/2015